




MiraSWAB®

1500 & 1600 Series Swabs



Description

MiraSWAB® 1500 and 1600 Series Swabs feature a patent-pending micro fiber fabric tip thermally bonded to a polypropylene shaft. The unique fabric over foam and fabric over fabric construction enables easy cleaning of scratch sensitive surfaces and blind areas as the two layers provide a soft conformable tool resulting in a swab that is soft, yet both resistant to abrasion and solvents. MiraSWABS® offer the cleaning performance of micro fiber fabrics with the scratch-free properties of foam for Optics, HDD, Semiconductor and Life Science applications.

HT15XXTC MiraSWAB® featuring micro fiber over a polyester fabric are recommended for cleaning optical surfaces when using methanol, ethyl ether or acetone.

The MiraSWAB® 1600 Series employs a static dissipative handle for ESD sensitive applications.



Common Characteristics & Benefits

- Fabric over foam construction compatible with aggressive solvents such as acetone, Kyzen and MEK.
- Super soft foam core enables the swabs to conform to articulated surfaces for good cleaning efficiency.
- Micro fiber fabric enables excellent removal of difficult to remove stains and particles.
- Proprietary cleaning process ensures low extractable for streak free cleaning.

Applications

- Cleaning stains and particles from scratch sensitive optics and optical assemblies.
- Cleaning applications that require acetone, MEK, NMP and Kyzen.
- Cleaning blind surfaces such as O-ring grooves and ink jet print heads.
- Replacing Cotton and Chamois swabs in applications requiring cotton like absorbency but without the fibers.
- Removing excess materials in fine assembly operations.



Foamtec International
720 Venture Dr.
Waco, TX 76712

Foamtec International WCC Division

1-760-599-7160

www.foamtecintlwcc.com | customerservice@foamtecintlwcc.com

Swab Models | Measured in Millimeters. ± 0.02

Part No.	HT1500FC	HT1501FC	HT1501TC	HT1502FC	HT1550C	HT1587TC	HT1602FC	HT1629FC	HT1639TC	HT1650FC
Image										
Head Material (Outer)	MiraWIPE®									
Head Material (Inner)	Foam		Polyester	Foam	MiraWIPE®	Polyester	Foam		Polyester	Foam
Head Thickness	4.9	3.3	2.9	2.7	2.2	5.2	2.7	2.3	3.3	2.3
Head Width	10.7	5.9	6.3	3.9	2.3	15.0	3.9	3.7	3.4	2.4
Head Length	21.8	10.4	17.0	10.4	10.5	24.0	10.4	10.8	9.1	10.5
Handle Material	Polypropylene					Polypropylene With Permanent ESD Additive				
Handle Diameter	2.9	2.9	2.9	2.5	2.5	6.9	2.5	2.5	3.0	2.5
Handle Length	120.0	133.7	134.5	58.9	58.1	102.5	59.1	58.1	79.6	57.9
Total Swab Length	141.8	151.5	151.5	69.3	68.6	126.5	69.5	68.9	88.7	68.4
Head Bond	Thermal									
Handle Color	Blue					White				
Description	Oval Tip	Flexible, Oval Tip	Flexible, Cylinder Tip	Flexible Tip	Pointed Tip	Semi-Rigid, Square Paddle Tip	Flexible Tip	Flexible Paddle Tip	Semi-Flexible Tip	Pointed Tip

Cleanliness

Particles (via LPC >.5µm)		Ionics (Via IC in mg/swab)	
<10k per swab		Chloride	< 0.9
		Sulfate	< 0.4
		Sodium	< 0.7
		Fluoride	< 0.4
		Nitrate	< 0.2
		Magnesium	< 0.2

TNVR's (mg/swab)	
In DI Water	In IPA
< 0.15	< 0.40

ESD Performance

Dissipation	1000 volts to 10 volts in less than 1 second at 50% RH
Volume Resistivity	1900 Static Dissipative Swabs - Handle - 10 ⁹



Foamtec International
720 Venture Dr.
Waco, TX 76712

Foamtec International WCC Division

1-760-599-7160

www.foamtecintlwcc.com | customerservice@foamtecintlwcc.com